

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Cancelled)

2. (Currently Amended) An electronic map apparatus comprising:

data fetching means for fetching map data from media for storing said map data to be displayed as a map;

a display device for displaying said map in a perspective view in accordance with said map data; and

a microcomputer for processing display data of an arc which is an equidistant curve from a center at a specified point on said map and links points on said perspective view at a constant distance corresponding to actual road distances from said center equal to those on said map,

~~wherein, when said map is displayed on said display device in said perspective view, said arc of equidistant curve is displayed on the basis of said arc's display data processed by said microcomputer being superimposed on said map displayed on said display device in a perspective view, and a corresponding distance from the center of said arc of equidistant curve is displayed in a plane view~~ said microcomputer is configured to selectively display said perspective view and a plane view on said display device, wherein in said perspective view, said arc of the equidistant curve is displayed on the basis of said arc's display data being superimposed on said map displayed on

said display device, and in said plane view, a corresponding distance from the center of said arc of equidistant curve is displayed on one of a plurality of said arcs of equidistant curves;

wherein said microcomputer is configured to process ~~processes~~ data of a plurality of arcs representing different geographical distances from said center and the arcs are each superposed on said map displayed in a perspective view;

wherein said microcomputer is configured to output ~~outputs~~ numbers each indicating a geographical distance from said center to one of said arcs and displays each of said numbers at a location in close proximity to the circumference of said arc with a geographical distance thereof indicated by said number;

wherein said microcomputer is configured to change ~~changes~~ contraction of a map displayed on said display device in a perspective view and modifies said geographical distances from said center to said arcs and the number of said arcs in accordance with a degree of contraction of said map;

wherein said microcomputer is configured to change ~~changes~~ a color of said arc into a supplementary color of a drawn portion to the distance display arc.

3. (Cancelled)

4. (Cancelled)

5. (Cancelled)

6. (Original) An electronic map apparatus according to claim 2, wherein:
said electronic map apparatus is a navigation apparatus mounted on a vehicle;
said specified point is the position of said vehicle;
map data of a map including said position of said vehicle is read out from said media; and
said map is displayed in a perspective view in accordance with said map data read out from said media.

7. (Original) An electronic map apparatus according to claim 2, wherein said specified point is a point on a map specified by a user.

8. (Previously Presented) An electronic map apparatus according to claim 2, wherein said map is displayed in a perspective view, and a character or a symbol representing a direction is displayed at said specified point.

9. (Currently Amended) An electronic map display method comprising the steps of:

fetching map data from predetermined media for storing said map data to be displayed as a map;

displaying said map on a display device in a perspective view in accordance with said map data; and

displaying an arc, which is an equidistant curve from a center at a specified point on said map and links points on said perspective view at a constant distance corresponding to actual road distances from said center equal to those on said map, and ~~displaying a corresponding distance from the center of said arc of equidistant curve in a plane view;~~ selectively displaying said perspective view and a plane view on said display device, in said perspective view, said arc of equidistant curve being displayed on the basis of said arc's display data being superimposed on said map displayed on said display device, and in said plane view, a corresponding distance from the center of said arc of equidistant curve being displayed on one of a plurality of said arcs of equidistant curves;

wherein a plurality of arcs representing different geographical distances from said center and the arcs are each displayed on said map displayed in a perspective view;

wherein numbers each indicating a geographical distance from said center to one of said arcs are displayed at a location in close proximity to the circumference of said arc;

wherein said geographical distances from said center to said arcs and the number of said arcs are changed in accordance with a degree of contraction of said map;

wherein ~~said microcomputer changes~~ changing a color of said arc into a supplementary color of a drawn portion to the distance display arc.

10. (Cancelled)

11. (Cancelled)

12. (Cancelled)

13. (Original) An electronic map display method according to claim 9, wherein:
the position of a vehicle on which a navigation apparatus is mounted is specified
as said specified point;

map data of a map including said position of said vehicle is read out from said
media; and

said map is displayed in a perspective view in accordance with said map data
read out from said media.

14. (Original) An electronic map display method according to claim 9, wherein a
point on map is specified by a user as said specified point.

15. (Original) An electronic map display method according to claim 9, wherein
said map is displayed in a perspective view, and a character or a symbol representing a
direction is displayed at said specified point.

16. (Previously Presented) The electronic map apparatus according to claim 2,
wherein a plurality of said arc is displayed so that the constant distance for each
equidistant curve corresponding to actual road distance is changed in accordance with
the perspective of the map being displayed on the display device in said perspective
view.

17. (Previously Presented) The electronic map display method according to claim 9, wherein a plurality of said arc is displayed so that the constant distance for each equidistant curve corresponding to actual road distance is changed in accordance with the perspective of the map being displayed on the display device in said perspective view.